



CHEMPIOIL

Product Code

8801

SYNCRO GLV

Synthetic Gear Oil

Meets the requirements:

SAE 75W-90
API GL-4/GL-5 LS (Limited Slip)
MACK GO-J
MACK GO-J Plus
MAN 342 M1
MAN 342 M2
MAN 342 M3
SCANIA STO 1:0

Volume:

1L, 4L, 20L, 60L, 208L, 1000L



Description:

A universal last-generation energy-conserving all-season synthetic gear oil for all types of manual transmissions. It is recommended for use in all types of synchronized manual transmissions (including heavy-duty), in differentials (including LS with excessive friction), steering equipment and other transmission parts where an excessive pressure and impact load is encountered and in which the use of standards GL-4 and/or GL-5 is prescribed.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	0.89
Viscosity at 40 °C	D 445	cSt	77.16
Viscosity at 100 °C	D 445	cSt	14.37
Viscosity index	D 2270		195
Flash point	D 92	°C	210
Pour point	D 97	°C	-45
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-
Brookfield dynamic viscosity at -40 °C, max	D 2983	cP(mPas)	148 000