



CHEMPIOIL

Product Code

8804

MTF-4

Synthetic Gear Oil

Meets the requirements:

SAE 75W-80
API GL-4
VOLKSWAGEN G 009 317
VOLKSWAGEN G 052 171/G 052 178
VOLKSWAGEN G 052 512/G 052 532
VOLKSWAGEN G 052 527/G 052 726
VOLKSWAGEN G 052 798/G 055 726
BMW MTF LT-1/-2/-3/-4
FORD WSS-M2C200-D2
MB 235.10
MITSUBISHI MZ312644 3005401
NISSAN 999MP-MTF20P KE91699932R
PEUGEOT 9730A2/9730A8
PSA B71 2330
TOYOTA JWS 227

Volume:

1L, 4L, 20L, 60L, 208L, 1000L



Description:

A latest-generation energy-conserving synthetic gear oil for manual transmissions. It is recommended for use in all types of 5- and 6-speed synchronized manual transmissions, including transmissions with an incorporated differential of front wheel drive vehicles, transfer cases and main gears, in which the application of the standard GL-4 is prescribed. It was developed on the basis of the requirements set by the BMW group.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	0.85
Viscosity at 40 °C	D 445	cSt	54.90
Viscosity at 100 °C	D 445	cSt	9.44
Viscosity index	D 2270		156
Flash point	D 92	°C	216
Pour point	D 97	°C	-46
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-
Brookfield dynamic viscosity at -40 °C, max	D 2983	cP(mPas)	34 500