



CHEMPIOIL

Product Code

8902

ATF D-III

Automatic Transmission Fluid

Meets the requirements:

ALLISON C4
ALLISON TES 389
CATERPILLAR TO-2
FORD Mercon V
FORD ESP-M2C138-CJ
FORD ESP-M2C166-H
GM Dexron III H
GM Dexron III G
GM Dexron III F
MB 236.1
VOITH H 55.6335.xx (G607)
ZF TE-ML 09
ZF TE-ML 11
ZF TE-ML 14

Volume:

1L, 4L, 20L, 60L, 208L



Description:

A universal all-season synthetic-based transmission fluid (ATF) for automatic gearboxes, hydraulic converters, hydraulic power steering systems, car hydraulic clutches and other hydraulic devices, including the ones operating under heavy-duty conditions in trucks and off-road vehicles. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy. It was developed on the basis of the requirements set by GM and Ford groups.

Product Characteristics:

Test	Method	Unit	Result
Color	visual		RED
Density at 15 °C	D 1298	kg/l	0.87
Viscosity at 40 °C	D 445	cSt	43.58
Viscosity at 100 °C	D 445	cSt	7.49
Viscosity index	D 2270		138
Flash point	D 92	°C	210
Pour point	D 97	°C	-46
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-
Brookfield dynamic viscosity at -40 °C, max	D 2983	cP(mPas)	19 000