



CHEMPIOIL

Product Code

9501

OPTIMA GT

Semi-Synthetic Motor Oil

Meets the requirements:

SAE 10W-40
API SN/CH-4
ACEA A3/B4
JASO MA2
VOLKSWAGEN 501 01
VOLKSWAGEN 502 00
VOLKSWAGEN 500 00
VOLKSWAGEN 505 00
MB 229.3
MB 229.1
PSA B71 2296
RENAULT RN0700
RENAULT RN0710

Volume:

1L, 4L, 5L, 20L, 60L, 208L



Description:

Innovative universal ester-containing motor oil on a hydrosynthetic basis for diesel engines, both new and "old" brands and with high mileage. Specially designed for turbocharged engines.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	Cst	103.78
Viscosity at 100 °C	D 445	Cst	14.97
Viscosity index	D 2270		150
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-40
Dynamic viscosity at -25 °C	D 5293	cP(mPas)	6454
Sulphate ash	D 874	% mass	1.02
Total base no.	D 2896	mgKOH/g	10.62
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	