

HYDRO ISO 46 LONGLIFE

Corresponds with requirements/ specifications/products:

ISO Viscosity Grade 46
DIN 51524-2 (HLP)
ISO 11158 (HM)
ASTM D6158
AFNOR FRANCE NF E 48-603
CONESTOGA ISO 20763
EATON I-286-S
MAG CINCINNATI P-70
PARKER DENISON HF-0
PARKER DENISON HF-1
PARKER DENISON HF-2
PARKER DENISON Filterability TP 02100
SPERRY VICKERS I-286-S
US STEEL 126
US STEEL 127
GB 11118.1
SEB 181222

Volume:

5L, 10L, 20L,
60L, 208L, 1000L



All-season mineral hydraulic oil created for hydraulic devices of stationary and mobile equipment operating in standard and high operating temperatures. It was developed taking into account the requirements for industrial hydraulic systems operating in the conditions of high loads, pressures, temperatures and/or velocities.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	890
Viscosity at 40 °C	D 445	cSt	45,18
Viscosity at 100 °C	D 445	cSt	6,77
Viscosity index	D 2270		104
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-33
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-

* For more information please contact our sales department.