

2103 HYDRO ISO 68 LONGLIFE

Corresponds with requirements/ specifications/products:

ISO Viscosity Grade 68
 DIN 51524-2 (HLP)
 ISO 11158 (HM)
 ASTM D6158
 AFNOR FRANCE NF E 48-603
 CONESTOGA ISO 20763
 EATON I-286-S
 MAG CINCINNATI P-69
 PARKER DENISON HF-0
 PARKER DENISON HF-1
 PARKER DENISON HF-2
 PARKER DENISON Filterability TP 02100
 SPERRY VICKERS I-286-S
 US STEEL 126
 US STEEL 127
 GB 11118.1
 SEB SEB 181222

Volume:

10L, 20L,
 60L, 208L, 1000L



All-season mineral hydraulic oil created for hydraulic devices of stationary and mobile equipment operating in standard and high operating temperatures. It was developed taking into account the requirements for industrial hydraulic systems operating in the conditions of high loads, pressures, temperatures and/or velocities.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	890
Viscosity at 40 °C	D 445	cSt	67,84
Viscosity at 100 °C	D 445	cSt	8,98
Viscosity index	D 2270		106
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-30
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-

* For more information please contact our sales department.