PRODUCT CODE

2901

COMPRESSOR OIL ISO 46



Corresponds with requirements / specifications / products:

ISO Viscosity Grade 46
BROWN BOVERI HTGD 90117
ISO DP 6521 (L-DAA), 6521 (L-DAB), 6521 (L-DAG), 6521 (L-DAH)
DIN 51506 (VBL), 51506 (VCL), 51506 (VDL), 51515-1 (L-TD), 51515-2 (L-TG), 51517-2 (CL), 51524-1,51524-2
VDMA 24568
SIEMENS TLV 9013
MAG CINCINNATI P-38, P-55, P-54, P-57, P-62
BSI GB BS 489
GE GEK 32568 A, GEK 32568 C
CEGB 207001
US STEEL 120
MITSUBISHI E00-87182
MIL L 17672 D
PARKER DENISON HF-0
AFNOR FRANCE NF E 48-603

Volume:

10L (FF2901-10) 20L (FF2901-20)
60L (FF2901-60) 208L (FF2901-DR)
1000L (FF2901-IBC)

Specials highly-purified paraffin ashless mineral compressor oil with an extended replacement age. It ensures a stable and continuous operation of the equipment throughout the entire operation period.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/m³	890
Viscosity at 100 °C	D 445	cSt	6,84
Viscosity index	D 2270		97
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-30
Viscosity at 40 °C, cSt	D 445	cSt	47,59