PRODUCT CODE

2902

COMPRESSOR OIL ISO 100



Corresponds with requirements / specifications / products:

ISO Viscosity Grade 100
DIN 51506 (VBL)
DIN 51506 (VCL)
DIN 51506 (VDL)
DIN 51515-1 (L-TD)
DIN 51515-2 (TG)
DIN 51517-2
DIN 51524-1
DIN 51524-2
ISO DP 6521 (DAA, DAB, DAH, DAG)
AFNOR FRANCE NF E 48-603
BSI GB BS 489
CEGB 207001
MIL L 17672 D
VDMA 24568
BROWN BOVERI HTGD 90117
GE GEK 32568 A
GE GEK 32568 C
MAG CINCINNATI P-38
MAG CINCINNATI P-55
MAG CINCINNATI P-54
MAG CINCINNATI P-57
MAG CINCINNATI P-62
MITSUBISHI E00-87182
PARKER DENISON HF-0
SIEMENS TLV 9013
US STEEL 120

Volume:

10L (FF2902-10) 20L (FF2902-20)
60L (FF2902-60) 208L (FF2902-DR)
1000L (FF2902-IBC)

Highly-purified paraffin low-ash mineral compressor oil with an extended replacement age. It ensures a stable and continuous operation of the equipment throughout the entire operation period.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/m³	890
Viscosity at 100 °C	D 445	cSt	10,76
Viscosity index	D 2270		93
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-25
Viscosity at 40 °C, cSt	D 445	cSt	97,55