TRD-15 SHPD

Corresponds with requirements/ specifications/products:

SAE 20W-50
API CI-4 Plus
API CI-4/CH-4/SL
ACEA E7
ACEA A3/B4
JASO DH-1
GLOBAL DHD-1
CATERPILLAR ECF-2 / ECF-1-a
CUMMINS CES 20076
CUMMINS CES 20077
CUMMINS CES 20078
DETROIT DIESEL 93K215
MACK EO-N
MACK EO-M Plus
MB 228.1
MB 228.3
MTU Type 2
RENAULT RLD-2
VOLVO VDS-3
MAN M 3275-1



Volume:

10L, 20L, 60L, 208L

Special multi-season, highly alloyed mineral engine oil with the addition of hydrosynthetics for modern, heavy duty and high-speed diesel engines with and without turbocharging, operating in extremely difficult conditions (including, at high ambient temperatures) and for engines with high mileage.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	890
Viscosity at 40 °C	D 445	cSt	153,2
Viscosity at 100 °C	D 445	cSt	17,88
Dynamic viscosity at -15 °C	D 5293	cP(mPas)	5875
Viscosity index	D 2270		130
Flash point COC	D 92	°C	230
Pour point	D 97	°C	-35
Total base no.	D 2896	mgKOH/g	10,99
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-

* For more information please contact our sales department.

SCT LUBRICANTS FOR FANFARO GMBH FELDSTRASSE 154, 22880 WEDEL, GERMANY TEL.: +49 4103 12110 WEB.: WWW.FANFARO.DE