6201

M-4T+

Corresponds with requirements/ specifications/products:

SAE 10W-40
API SL
JASO MA/MA2



Volume:

1L, 20L,
60L, 208L

An innovative synthetic ester-containing engine oil for 4-stroke high-load engines of motorcycles, pit bikes, motards, etc. for off-road (enduro, motocross, trials, etc.) and highway (stuntriding, supermoto, etc.) driving under extreme loads. It was designed for a guaranteed protection of the engine and the durability of the gearbox.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	90,51
Viscosity at 100 °C	D 445	cSt	13,52
Dynamic viscosity at -25 °C	D 5293	cP(mPas)	5879
Viscosity index	D 2270		151
Flash point COC	D 92	°C	222
Pour point	D 97	°C	-38
Total base no.	D 2896	mgKOH/g	8,18
Ignition temperature, not below		°C	350
Sulphate ash	D 874	% mass	0,84
High-shear-rate viscosity at 150 °C	D 24741	cP(mPas)	3,60

SCT LUBRICANTS FOR FANFARO GMBH FELDSTRASSE 154, 22880 WEDEL, GERMANY TEL.: +49 4103 12110 WEB.: WWW.FANFARO.DE