6208

S-4T+

Corresponds with requirements/ specifications/products:

SAE 20W-50
API SN
JASO MA/MA2



Volume:

1L, 20L,
60L, 208L, 1000L

A universal all-season synthetic-based engine oil for 4-stroke normal- and high-load engines (including 2-cylinder V-type) for highway, off-road and racing motorcycles. It was designed for a guaranteed protection of the engine and the durability of the gearbox.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	890
Viscosity at 40 °C	D 445	cSt	155,0
Viscosity at 100 °C	D 445	cSt	17,29
Dynamic viscosity at -15 °C	D 5293	cP(mPas)	7528
Viscosity index	D 2270		121
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-34
Total base no.	D 2896	mgKOH/g	8,18
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-
High-shear-rate viscosity at 150 °C	D 24741	cP(mPas)	7528

SCT LUBRICANTS FOR FANFARO GMBH FELDSTRASSE 154, 22880 WEDEL, GERMANY TEL.: +49 4103 12110 WEB.: WWW.FANFARO.DE