



Corresponds with requirements/ specifications/products:

SAE 10W-30
API SP (RC)
ILSAC GF-6A
ACEA A3/B4
VOLKSWAGEN 505 00
VOLKSWAGEN 501 01
CHRYSLER MS-6395
MB 229.1
ISUZU
KIA
TOYOTA
MAZDA
HONDA
NISSAN
SUBARU
SUZUKI
SSANGYONG
MITSUBISHI
HYUNDAI
DAEWOO



Volume:

1L, 4L, 5L, 7L,
20L, 208L, 1000L

Hydro-synthetic universal motor oil for all types of gasoline engines. Designed to meet VW and DAIMLER requirements.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	75,77
Viscosity at 100 °C	D 445	cSt	11,41
Dynamic viscosity at -25 °C	D 5293	cP(mPas)	6364
Viscosity index	D 2270		142
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-40
Total base no.	D 2896	mgKOH/g	10,55
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-
Sulphate ash	D 874	% mass	1,1

* For more information please contact our sales department.