6701 LSX

FANFARO

Corresponds with requirements/ specifications/products:

SAE 5W-30
API SN
ACEA C3
MB 229.51
VOLKSWAGEN 504 00
VOLKSWAGEN 507 00
VOLKSWAGEN TL 52 195
BMW LL-04
PORSCHE C30



Volume:

1L, 4L, 5L, 20L,
60L, 208L, 1000L

Longlife engine oil for modern gasoline and diesel engines (including those with direct injection) with and without turbocharging, including those equipped with pump nozzles (Pumpe-Duse). Designed based on VW and DAIMLER requirements.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	70,50
Viscosity at 100 °C	D 445	cSt	11,62
Dynamic viscosity at -30 °C	D 5293	cP(mPas)	6580
Viscosity index	D 2270		160
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-48
Total base no.	D 2896	mgKOH/g	8,74
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-

* For more information please contact our sales department.

SCT LUBRICANTS FOR FANFARO GMBH FELDSTRASSE 154, 22880 WEDEL, GERMANY TEL.: +49 4103 12110 WEB.: WWW.FANFARO.DE