6702 VSX

FANFARO

Corresponds with requirements/ specifications/products:

SAE 5W-40
ACEA A3/B4
MB 229.5/229.3/226.5
JASO MA2
VOLKSWAGEN 502 00/505 00
PORSCHE A40
RENAULT RN0700
RENAULT RN0710
API SN/CH-4
BMW LL-01/-98
PSA B71 2296
FIAT 9.55535-H2/-Z2
CHRYSLER MS-10850
CHRYSLER MS-10896
CHRYSLER MS-12991
GM LL-A-025/-B-025



Volume:

1L, 4L, 5L, 10L, 20L,
60L, 208L, 1000L

Innovative, universal, premium ester-containing engine oil for modern gasoline and diesel engines with and without turbocharging, including “old” brands and high mileage. Designed based on the requirements of European producers.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	82,61
Viscosity at 100 °C	D 445	cSt	13,40
Dynamic viscosity at -30 °C	D 5293	cP(mPas)	5996
Viscosity index	D 2270		165
Flash point COC	D 92	°C	236
Pour point	D 97	°C	-42
Total base no.	D 2896	mgKOH/g	10,66
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-

* For more information please contact our sales department.

SCT LUBRICANTS FOR FANFARO GMBH FELDSTRASSE 154, 22880 WEDEL, GERMANY TEL.: +49 4103 12110 WEB.: WWW.FANFARO.DE