



Corresponds with requirements/ specifications/products:

SAE 10W-40
API SN/CH-4
ACEA A3/B4
JASO MA2
VOLKSWAGEN 505 00
VOLKSWAGEN 502 00
VOLKSWAGEN 501 01
VOLKSWAGEN 500 00
MB 229.3
MB 229.1
PSA B71 2296
RENAULT RN0710
RENAULT RN0700

Volume:

1L, 4L, 5L, 10L,
20L, 60L, 208L, 1000L



Universal ester-containing synthetic engine oil for modern gasoline and diesel engines with and without a turbocharger, both multi-valve and direct injection, including "old" brands and high mileage vehicles. Designed according to the requirements of European manufacturers.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	93,54
Viscosity at 100 °C	D 445	cSt	13,78
Dynamic viscosity at -25 °C	D 5293	cP(mPas)	6062
Viscosity index	D 2270		149
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-38
Total base no.	D 2896	mgKOH/g	10,01
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-

* For more information please contact our sales department.