FANFARO

6705

PDX

Corresponds with requirements/ specifications/products:

SAE 5W-40
API SN
ACEA C3
ACEA C2
MB 229.51/229.31
MB 226.5
BMW LL-04
GM dexos2
VOLKSWAGEN 505 01
VOLKSWAGEN 505 00
RENAULT RN0700
RENAULT RN0710
FORD WSS-M2C917-A
PORSCHE A40
FIAT 9.55535-S2
FIAT 9.55535-GH2
CHRYSLER MS-11106



Volume:

1L, 5L, 20L,
60L, 208L, 1000L

Innovative universal energy-saving ester-containing fully synthetic premium motor oil for modern diesel engines (including those with direct injection) and gasoline engines with and without turbocharging, including those equipped with pump nozzles (Pumpe-Duse). Designed based on VW and DAIMLER requirements.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	81,39
Viscosity at 100 °C	D 445	cSt	13,40
Dynamic viscosity at -30 °C	D 5293	cP(mPas)	5980
Viscosity index	D 2270		167
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-42
Total base no.	D 2896	mgKOH/g	8,36
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-
Noakc volatility test, %	D 5800	mass/mass	11,3
Acid number	D 664	mgKOH/g	1,06
High-shear-rate viscosity at 150 °C	D 4741	cP	3,60

* For more information please contact our sales department.

SCT LUBRICANTS FOR FANFARO GMBH FELDSTRASSE 154, 22880 WEDEL, GERMANY TEL.: +49 4103 12110 WEB.: WWW.FANFARO.DE