

Corresponds with requirements/ specifications/products:

SAE 5W-30
API SN/CH-4
ACEA C2
ACEA C3
VOLKSWAGEN 505 01
BMW Longlife-04
MB 229.52
MB 229.51
MB 229.31
MB 226.5
GM dexos2
RENAULT RN0700
RENAULT RN0710

Volume:

1L, 5L, 20L,
60L, 208L, 1000L



Innovative, versatile, all-synthetic ester-containing premium synthetic engine oil for modern diesel and gas turbocharged and non-turbocharged engines. Designed in accordance with the requirements of European automakers.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	72,12
Viscosity at 100 °C	D 445	cSt	12,0
Dynamic viscosity at -30 °C	D 5293	cP(mPas)	5936
Viscosity index	D 2270		164
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-42
Total base no.	D 2896	mgKOH/g	8,87
Ignition temperature, not below	D 5185	°C	350
Calcium Ca	D 5185	ppm	4691
Zinc Zn	D 5185	ppm	821
Magnesium Mg	D 5185	ppm	26
Molybdenum Mo	D 5185	ppm	34

* For more information please contact our sales department.