6724

NSX

Corresponds with requirements/ specifications/products:

SAE 0W-20
API SP (RC)
ILSAC GF-6A
HONDA HTO-06
GM Dexos1 Gen 3
GM 6094M
CHRYSLER MS-6395
CHRYSLER MS-13340
JAGUAR STJLR.51.5122
LAND ROVER STJLR.51.5122
FORD WSS-M2C947-A
FORD WSS-M2C947-B1
INFINITI
LEXUS
MAZDA
SUZUKI



Volume:

1L, 4L, 20L,
60L, 208L

Innovative energy-saving premium bi-synthetic engine oil (PAO + esters) for modern gasoline engines. Designed to meet the requirements of American, Japanese and Korean automakers.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	833
Viscosity at 40 °C	D 445	cSt	45,01
Viscosity at 100 °C	D 445	cSt	8,43
Dynamic viscosity at -35 °C	D 5293	cP(mPas)	6180
Viscosity index	D 2270		167
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-46
Total base no.	D 2896	mgKOH/g	8,33
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-
High-shear-rate viscosity at 150 °C	D 4741	cP	2,76

* For more information please contact our sales department.

SCT LUBRICANTS FOR FANFARO GMBH FELDSTRASSE 154, 22880 WEDEL, GERMANY TEL.: +49 4103 12110 WEB.: WWW.FANFARO.DE