6726

XTR

Corresponds with requirements/ specifications/products:

SAE 0W-30
API SN Plus
API SP
ACEA C2
ACEA C3
BMW LL-12FE
MB 229.61
FORD WSS-M2C950-A
OPEL OV0401547
PSA B71 2290
PSA B71 2312



Volume:

1L, 5L, 20L,
60L, 208L

Premium PAO-based engine oil for modern diesel- and petrol-powered engines of vehicles produced by European manufacturers with and without a turbocharger.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	69,03
Viscosity at 100 °C	D 445	cSt	12,29
Dynamic viscosity at -35 °C	D 5293	cP(mPas)	6180
Viscosity index	D 2270		178
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-45
Total base no.	D 2896	mgKOH/g	8,28
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-
High-shear-rate viscosity at 150 °C	D 4741	cP	3,52

* For more information please contact our sales department.

SCT LUBRICANTS FOR FANFARO GMBH FELDSTRASSE 154, 22880 WEDEL, GERMANY TEL.: +49 4103 12110 WEB.: WWW.FANFARO.DE