6729

Fully Synthetic Premium Engine Oil

SAE 0W-30

Corresponds with requirements/ specifications/products:

SAE 0W-30
ACEA C3
MB 229.52
MB 229.51
MB 229.31
VOLKSWAGEN 504 00
VOLKSWAGEN 507 00
VOLKSWAGEN TL 52545
BMW Longlife-04
PORSCHE C30



Volume:

1L, 5L, 20L, 60L, 208L

Innovative energy-saving bi-synthetic (PAO + ester) premium engine oil with improved low-temperature properties for modern gasoline and diesel engines (including those with direct injection) with and without turbocharging, including those equipped with pump-injectors (Pumpe-Düse). Developed based on the requirements of VW and DAIMLER.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	66,21
Viscosity at 100 °C	D 445	cSt	11,88
Dynamic viscosity at -35 °C	D 5293	cP(mPas)	5829
Viscosity index	D 2270		178
Flash point	D 92	°C	238
Pour point	D 97	°C	-51
Total base no.	D 2896	mgKOH/g	8,17
High-shear-rate viscosity at 150 °C	D 4741	°C	3,52
Sulphate ash	D 874	% mass	0,7
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-

* For more information please contact our sales department.