FANFARO

8601

CVT

Corresponds with requirements/ specifications/products:

VOLKSWAGEN G 052 180
BMW 83 22 0 429 154/CVT EZL 799A
CHRYSLER CVT FLUID NS-2
DAIHATSU AMIX CVT FLUID DC
FORD WSS M2C928-A/M2C933-A/CVT FLUID 23/30, Mercon C
GM DEX-CVT
HONDA HMMF (08260-99904)/HCF-2
HYUNDAI ATF SP-III
INFINITI null
JEEP CVT FLUID NS-2
KIA ATF-SP-III
LEXUS null
MAZDA CVT FLUID JWS 3320
MB 236.20
MINI CVT EZL 799A/83 22 0 429 154
MITSUBISHI DIAQUEEN CVT FLUID J1/J4/CVT ATF SP-III
MOPAR CVTF +4
NISSAN CVT FLUID NS-1/NS-2 (KLE52-00004)
SUBARU CVT OIL FOR LINEARTRONIC (K0425Y0710)/I-CVT FLUID
SUBARU I-CVT FLUID FG/SCVT FLUID/CVT OIL/CVT FLUID GREEN 1/2
SUZUKI NS-2
TOYOTA CVT FLUID TC/FE



Volume:

1L, 20L,
60L, 208L, 1000L

A special synthetic gear oil for CVT (Continuously Variable Transmission) – variable-speed gears. It was specially developed for use in continuously variable transmissions with a rigid articulated chain or a steel pull chain. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of a transmission and fuel economy.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	34,94
Viscosity at 100 °C	D 445	cSt	7,03
Brookfield dynamic viscosity at -40 °C	D 2983	cP(mPas)	19 000
Viscosity index	D 2270		168
Flash point COC	D 92	°C	210
Pour point	D 97	°C	-45
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-

* For more information please contact our sales department.

SCT LUBRICANTS FOR FANFARO GMBH FELDSTRASSE 154, 22880 WEDEL, GERMANY TEL.: +49 4103 12110 WEB.: WWW.FANFARO.DE