



Corresponds with requirements/ specifications/products:

JASO M315 Type 1A, AISIN WARNER JWS 3309, VW G 052 025-A2, VW G 052 162-A1, VW G 052 990-A1, VW G 052 990-A2, GM Dexron II D, VW G 055 025-A1/-A2, BMW 83 22 0 403 248, BMW 83 22 2 163 514, BMW 83 22 9 407 765 (LA 2634), BMW 83 22 9 407 807, GM Dexron II E, BMW 7045E (3 Series), BMW ETL-8072B (5 Series), CHRYSLER ATF+3, BMW LT71141 (ZF 5 Speed), CHRYSLER ATF+4, FORD Mercon V, DAIHATSU ALUMIX ATF MULTI, FORD Mercon SP, FORD Mercon LV, FORD Mercon ATF Type F, FORD XT-8-QMM5 [FRN5], GM Dexron II, GM Dexron III F/G/H, HONDA ATF-Z1 (not for CVT), HONDA ATF DW-1, HYUNDAI ATF SP-II/-III, IDEMITSU K17-Jaguar X Type 2001-2005, INFINITI Matic D/J/K, JATCO ATF 3100 PI085, KIA ATF-SP-II/-III, MAN 339 F/V1/V2/Z1/Z2, MAZDA ATF M-III, MAZDA ATF M-V, MB 236.1, MB 236.2, MB 236.3, MB 236.5, MB 236.6, MB 236.7, MB 236.9, MB 236.10/236.11, MITSUBISHI DIAMOND SP-II/-III, MOPAR AS68RC, NISSAN Matic D/J/K, PORSCHE JWS 3309, SUBARU ATF-5, SUBARU ATF-HP, SUZUKI 3314/3317/2384K, SUZUKI ATF OIL, SUZUKI ATF OIL SPECIAL, TOYOTA ATF Type T, TOYOTA ATF Type T-II, TOYOTA ATF Type T-III, TOYOTA ATF Type T-IV, LEXUS ATF Type T, LEXUS ATF Type T-II/-III/-IV, VOITH 55.6335.XX (G607), VOLVO 97340, VOLVO 97341, ZF TE-ML 03D, ZF TE-ML 04D, ZF TE-ML 11B, ZF TE-ML 14A, ZF TE-ML 14B, ZF TE-ML 16L, ZF TE-ML 17, Others TEXACO N402 (JATCO FWD)/ETL 7045E/ETL 8072B/ MOBIL ATF LT 71141



Volume:

1L, 4L, 20L, 60L, 208L, 1000L

A universal all-season high-viscosity synthetic transmission fluid (ATF) for automatic gearboxes. It was specially developed for all modern automatic gearboxes (manual or sequential modes, electronic control, etc.) equipped with and without a hydraulic converter lock-up. It is also compatible with old-generation automatic gearboxes, hydraulic power steering systems, ship reversing gears, hydrostatic transmissions, hydraulic/mechanical systems in which the use of fluids that correspond to Dexron (except Dexron VI) or Mercon standards is prescribed. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy. It was developed on the basis of the requirements set by the company AISIN WARNER.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	34,96
Viscosity at 100 °C	D 445	cSt	6,59
Brookfield dynamic viscosity at -40 °C	D 2983	cP(mPas)	15 500
Viscosity index	D 2270		168
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-48
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-

* For more information please contact our sales department.