



Corresponds with requirements/ specifications/products:

ALLISON C4
 CATERPILLAR TO-2
 GM Dexron II D
 MAN 339 V1
 MAN 339 Z1
 MB 236.5
 MB 236.7
 RENK
 VOITH H 55.6335.xx (G607)
 ZF TE-ML 03D
 ZF TE-ML 04D
 ZF TE-ML 11A
 ZF TE-ML 14A
 ZF TE-ML 17C

Volume:

1L, 4L, 20L,
 60L, 208L, 1000L



A universal all-season mineral-based transmission fluid (ATF) for automatic gearboxes, hydraulic power steering systems, cab tilt mechanisms, car hydraulic clutches and other hydraulic devices, including the ones operating under heavy-duty conditions in trucks and off-road vehicles.

Product Characteristics:

Characteristics	Method	Unit	Value
Color	visual		RED
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	48,82
Viscosity at 100 °C	D 445	cSt	7,74
Brookfield dynamic viscosity at -40 °C	D 2983	cP(mPas)	45 000
Viscosity index	D 2270		137
Flash point COC	D 92	°C	208
Pour point	D 97	°C	-46
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-

* For more information please contact our sales department.