

AZF8

Corresponds with requirements/ specifications/products:

JASO -M315, Class 1-A-LV, AISIN WARNER AW-2, AISIN WARNER, JWS 3309 ATF, ATF-0T4/JWS 3324 ATF, ATF-0WS, ALLISON C2, ALLISON C3/C4, ATF 134/3353, ISUZU SCS, ATF 3100 PL085/3403-M115, ATF N402, ATF D971/ETL-7045 E/K17/L12108/LA 2634 ATF M-1375.4/M-1375.6, BENTLEY PY112995PA, BMW ATF4, BMW 83 22 2 220 442, BMW 83 22 2 289 720/305 396/305 397/355 599/355 601, BMW ATF 3+, BMW ETL-7045, BMW 83 22 7 542 290/9 407 765/9 407 807, BMW ETL-7045 E, BMW ATF6, BMW LA 2634, BMW LT 71141/M-L12108, BMW 81 22 9 400 272, BMW ETL-8072B, BMW 81 22 9 400 275, BMW 81 22 9 407 858/9 407 859, BMW 83 22 0 024 249, BMW 83 22 0 024 359/026 922, BMW 83 22 0 142 516/397 114/402 413/403 248/403 249/2 152 426/2 163 514/2 220 438, BMW 83 2 220 440, BOSCH TE-ML 09, CITROEN Z 000169756, DAIHATSU D3-SP, ISUZU ATF III, FCA 8 & 9 Speed ATF, 68218925AA/68218925AB, FCA ASRC/ATF+, FCA ATF+2/ATF+3, FCA ATF+4, FCA AW-1 68092912AA, FCA ATF+4, FCA DEX-VI 68043742AA, HYUNDAI SP, FCA MB 236.10/12 05127382AA, FCA SP-III, FCA 05127382/68157995AA/68157995AB, FCA 68333587AA, FCA SP-4 68171866AA/-IV, 68171866AA/-IV, 68171869AA/Type 7176E, FCA Type 9602, FCA ESP-M2C138-CJ, FCA ESP-M2C166-H, FORD XT-10-QLV [LV], ISUZU ATF II, FORD XT-12-ULV [ULV]/-2-QDX [M]/-2-QDM [Syn]/-5-QM [V]/-5-QSM [V Syn], GM WS, KIA SP-IV, FORD XT-6-QSP [SP]/-8-QAW [Premium]/-9-QMM5 [FRN5], GM AW-1 19256039, KIA SP4-M1, FORD Spec WSS-M2C922-A1, GM ATF Z1, Saturn 22717466, GM Dex [GM 6032M], KIA SP-II, GM DEX HP [GMW 16974]/ULV, 19352619/-B [GM 6032M]/-IIC [6137M]/-IID [GM 6137M], GM DEX-IIIE [GM 6137M]/-IIIF [GM 6297M]/-IIIG [GM 6417M]/-IIIH [GM N10055]/-VI [GMW 16444], GM 19 40 700/767, GM 21005966/88900925/9985010/9986195, GM Saturn T-IV Fluid, KIA SP-II, GM Saturn 22689186, GLOBAL Type A Suffix A/88863400/88863401, HYUNDAI 04500-00140, HONDA ATF DW-1 08200-9008/Type 3.0 08200-9016-A/Type 3.1 08200-9017-A/Z1, 08200-9001, HONDA ATF Z1, 08200-9001A, ACURA ATF DW-1 08200-9008, ACURA ATF Type 3.0 08200-9016-A, ACURA ATF Type 3.1 08200-9017, ACURA ATF Z1, 08200-9001, ACURA ATF Z1, 08200-9001A, HYUNDAI ATF RED-1K/SP-IV/Genuine ATF/JWS 3314/00232-19023/040000C90SG, KIA SP, HYUNDAI UM040 CH20 Red-1, HYUNDAI SP4-M1/-IV, HYUNDAI SP-II/-III/-IV/-RR, KIA SPH-IV, HYUNDAI WS, spec NWS-9638, KIA ATF RED-1K/SP-IV, KIA Genuine ATF, KIA JWS 3314, KIA 00232-19023/040000C90SG/04500-00140/UM040 CH20 Red-1, KIA WS, spec NWS-9638, ISUZU Genuine ATF/08200-9001, JAGUAR 02JDE 26444/Fluid 8432/JML 20238/JLM 20292, JAGUAR JLM 21044/K17, Jatco 3100 PL085/LT 71141/WSS-M2C922-A1, LAND ROVER ATF N402, LAND ROVER AW-1 LR0022460: LV/JWS3309US/TYK500050/LR023288/LR023289, MAN 339A, MAN 339D/F, MASERATI Oil No. 231603, MAZDA ATF A7/M-5 0000-23-ATF-M5 and many others

Volume: 1L, 20L, 208L

A special all-season synthetic transmission fluid (ATF) for modern 8-speed automatic gearboxes of all types and 6-speed automatic gearboxes of the ZF Group. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy even under extreme loads. It was developed taking into account special requirements set by the VW Group.



Product Characteristics:

Characteristics	Method	Unit	Value
Color	visual		GREEN
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	26,93
Viscosity at 100 °C	D 445	cSt	5,79
Brookfield dynamic viscosity at -40 °C	D 2983	cP(mPas)	10 550
Viscosity index	D 2270		166
Flash point COC	D 92	°C	218
Pour point	D 97	°C	-50
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-

* For more information please contact our sales department.