FANFARO

8615

ATF VI

Corresponds with requirements/ specifications/products:

JASO M315, Class 1-A-LV, AISIN WARNER JWS 3309, AISIN WARNER JWS 3324
AISIN WARNER ATF-0T4, AISIN WARNER ATF-0WS, CITROEN Z 000169756
ALLISON C3, ALLISON C2, ALLISON C4, BENTLEY PY112995PA, BOSCH TE-ML 09
FORD XT-8-QAW [Premium], FORD XT-9- QMM5 [FRN5], FORD WSS-M2C922-A1
FORD Mercon LV, FORD ESP-M2C138-CJ, FORD ESP-M2C166-H, FORD XT-10-QLV [LV]
FORD XT-2-QDX [M], FORD XT-2-QSM [Syn], FORD XT-5-QM [V], FORD XT-5-QSM [V Syn]
FORD XT-6-QSP [SP], GM Type A Suffix A, GM Saturn T-IV Fluid, GM Saturn 22689186
GM ATF Z1, GM Saturn 22717466, GM Dex-VI [GMW 16444], GM AW-1
GM Dex [GM 6032M], GM Dex-B [GM 6032M], GM 19256039, GM Dex-IIC [6137M]
GM Dex-IID [GM 6137M], GM Dex-IIE [GM 6137M], GM ATF WS, GM Dex-IIIF [GM 6297M]
GM Dex-IIIG [GM 6417M], GM Dex-IIIH [GM N10055], GM 88863400, GM 19 40 700
GM 19 40 767, GM 21005966, GM 88863401, GM 88900925, GM 9985010, GM 9986195
HYUNDAI ATF SP-IV, HYUNDAI ATF RED-1K, HYUNDAI Genuine ATF, HYUNDAI JWS 3314
HYUNDAI 00232-19023, HYUNDAI 040000C90SG, HYUNDAI 04500-00140, HYUNDAI SP
HYUNDAI UM040 CH20 Red-1, HYUNDAI SP4-M1, HYUNDAI SPH-IV, HYUNDAI SP-II
HYUNDAI SP-III, HYUNDAI SP-IV, HYUNDAI SP-IV-RR, HYUNDAI WS, spec NWS-9638
KIA SP-IV, KIA ATF RED-1K, KIA ATF SP-IV, KIA Genuine ATF, KIA JWS 3314
KIA 00232-19023, KIA 040000C90SG, KIA 04500-00140, KIA SP, KIA UM040 CH20 Red-1
KIA SP4-M1, KIA SPH-IV, KIA SP-II, KIA SP-III, KIA SP-IV-RR, KIA WS, spec NWS-9638
TOYOTA ATF WS Lifetime, TOYOTA JWS 3324, TOYOTA ATF FZ, TOYOTA JWS 3309
TOYOTA 08886-81015, TOYOTA Type T, T-II, T-III, T-IV, TOYOTA Type D-II, MB 236.14
MB A 0019892203, MB ATF 3403-M115, MB 236.1, MB 236.10, MB 236.11, MB 236.12
MB 236.15, MB 236.2, MB 236.41, MB 236.5, MB 236.8, NISSAN Matic S
VOLKSWAGEN LT 71141, VOLKSWAGEN G 052 162 [Ag4], VOLKSWAGEN G 052 533
VOLKSWAGEN G 052 990 A2, VOLKSWAGEN G 055 005 A2, VOLKSWAGEN G 055 025 A2
VOLKSWAGEN G 055 162 A2, VOLKSWAGEN G 055 540 A2, VOLKSWAGEN G 060 162 A2
VOLKSWAGEN G US 000 162, NISSAN Fluid A, NISSAN Matic D, NISSAN Matic J
NISSAN Matic K, NISSAN Matic W, NISSAN N402, NISSAN 999MP-MTJ00P, 999MP-MTS00P
BMW ATF 3+, BMW ATF4, BMW ATF6, BMW ETL-7045, BMW ETL-7045 E and many others



Volume:

1L, 20L, 208L, 1000L

A universal all-season synthetic transmission fluid (ATF) for automatic gearboxes, hydraulic converters, hydraulic power steering systems, car hydraulic clutches and other hydraulic devices, including the ones operating in heavy-duty conditions in trucks and off-road vehicles.

Product Characteristics:

Characteristics	Method	Unit	Value
Color	visual		RED
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	30,94
Viscosity at 100 °C	D 445	cSt	6,15
Brookfield dynamic viscosity at -40 °C	D 2983	cP(mPas)	9960
Viscosity index	D 2270		152
Flash point COC	D 92	°C	214
Pour point	D 97	°C	-52
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-

* For more information please contact our sales department.

SCT LUBRICANTS FOR FANFARO GMBH FELDSTRASSE 154, 22880 WEDEL, GERMANY TEL.: +49 4103 12110 WEB.: WWW.FANFARO.DE