

Product Code:

FF 8703

FANFARO MAX 5



Corresponds with requirements / specifications / products:

SAE 80W-90
API MT-1
API GL-4/GL-5 LS (Limited Slip)
MIL-L-2105 D
MACK GO-J
MAN 342, MAN 342 Type M2
MAN 341 Type E2, MAN 341 Type Z2
ZF TE-ML 02B, 05A, 12L, 16B, 17B, 19B, 21A
SCANIA STO 1:0
MB 235.0 (DTFR 12B100)
DAF, IVECO, VOLVO

Volume:

1L, 4L, 10L, 20L,
60L, 208L, 1000L

A universal all-season mineral-based gear oil. It was developed for hypoid gears withstanding extreme loads; in heavy-duty bevel, cylindrical and worm pairs. It is recommended for use in differentials (including excessive friction – LS). It may be used for all types of manual transmissions, including the ones withstanding extremely heavy loads and high temperatures and in other transmission parts where extreme pressure and impact loads are encountered.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/m ³	890
Viscosity at 40 °C	D 445	cSt	161,51
Viscosity at 100 °C	D 445	cSt	16,82
Brookfield dynamic viscosity at -26 °C	D 2983	cP(mPas)	145 000
Viscosity index	D 2270		111
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-32
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	

* For more information please contact our sales department.