8706

MAX6

Corresponds with requirements/ specifications/products:

SAE 75W-90
API GL-4 / GL-5 (Limited Slip)
MACK GO-J
MACK GO-J Plus
MAN 342 Type M2
MAN 342 Type M3
SCANIA STO 1:0



Volume:

1L, 20L, 60L, 208L, 1000L

A universal last-generation energy-conserving all-season synthetic gear oil for all types of manual transmissions. It is recommended for use in all types of synchronized manual transmissions (including heavy-duty), in differentials, steering equipment and other transmission parts where an excessive pressure and impact load is encountered and in which the use of standards GL-4 and/or GL-5 is prescribed.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	890
Viscosity at 40 °C	D 445	cSt	85,42
Viscosity at 100 °C	D 445	cSt	15,03
Brookfield dynamic viscosity at -40 °C	D 2983	cP(mPas)	148 000
Viscosity index	D 2270		186
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-42
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-

* For more information please contact our sales department.

SCT LUBRICANTS FOR FANFARO GMBH FELDSTRASSE 154, 22880 WEDEL, GERMANY TEL.: +49 4103 12110 WEB.: WWW.FANFARO.DE