

Product Code:

2101

HYDRO ISO 32

Hydraulic Oil

Meets the requirements:

ISO Viscosity Grade 32, DIN 51524 Part 1,
ISO-L-HL (11158 : 2023), FIVES CINCINNATI MACHINE P-38,
DIN 51517-2 (CL), AFNOR FRANCE NF E 48-603,
CONESTOGA ISO 20763, SPERRY VICKERS I-286-S,
EATON I-286-S, MAG CINCINNATI P-68/-69/-70,
PARKER DENISON HF-0/-1/-2, US STEEL 126/127,
PARKER DENISON Filterability TP 02100

All-season mineral hydraulic oil created for hydraulic devices of stationary and mobile equipment operating in standard and high operating temperatures. It was developed taking into account the requirements for industrial hydraulic systems operating in the conditions of high loads, pressures, temperatures and/or velocities.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/m ³	870
Viscosity at 40 °C	D 445	CSt	33.19
Viscosity at 100 °C	D 445	CSt	5.62
Viscosity index	D 2270		107
Flash point COC	D 92	°C	208
Pour point	D 97	°C	-36
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-

Volume:

5L	MN2101-5	60L	MN2101-60
10L	MN2101-10	208L	MN2101-DR
20L	MN2101-20	1000L	MN2101-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®