

Product Code:

2102

HYDRO ISO 46 LONGLIFE

Hydraulic Oil

Meets the requirements:

ISO Viscosity Grade 46, DIN 51524-2 (HLP), ISO 11158 (HM), ASTM D6158, AFNOR FRANCE NF E 48-603, CONESTOGA ISO 20763, EATON I-286-S, MAG CINCINNATI P-70, PARKER DENISON HF-0, PARKER DENISON HF-1, PARKER DENISON HF-2, US STEEL 126/127, PARKER DENISON Filterability TP 02100, SPERRY VICKERS I-286-S, GB 111118.1, SEB 181222

All-season mineral hydraulic oil created for hydraulic devices of stationary and mobile equipment operating in standard and high operating temperatures. It was developed taking into account the requirements for industrial hydraulic systems operating in the conditions of high loads, pressures, temperatures and/or velocities.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	46.97
Viscosity at 100 °C	D 445	cSt	7.16
Viscosity index	D 2270		111
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-36
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-

Volume:

5L	MN2102-5	60L	MN2102-60
10L	MN2102-10	208L	MN2102-DR
20L	MN2102-20	1000L	MN2102-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®