

Product Code:

2104

HYDRO ISO 100

Industrial Hydraulic Oil

Meets the requirements:

ISO Viscosity Grade 100, DIN 51524-2 (HLP), ISO 11158 (HM),
AFNOR FRANCE NF E 48-603, CONESTOGA ISO 20763,
MAG CINCINNATI P-68/-69/-70, PARKER DENISON HF-0/-1/-2,
PARKER DENISON Filterability TP 02100, US STEEL 126/127,
SPERRY VICKERS I-286-S, EATON I-286-S

Special all-season mineral hydraulic oils created for hydraulic devices of stationary or mobile equipment operating at high and very high operating temperatures. It was developed taking into account the requirements for industrial hydraulic systems operating in the conditions of very high loads, pressures, temperatures and/or velocities.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	890
Viscosity at 40 °C	D 445	cSt	94.88
Viscosity at 100 °C	D 445	cSt	11.331
Viscosity index	D 2270		106
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-28
Ignition temperature	D 2273	°C	350
Mechanical impurities	D 2273	%	-

Volume:

10L	MN2104-10	60L	MN2104-60
20L	MN2104-20	208L	MN2104-DR
		1000L	MN2104-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®