Product Code:

2203

HYDRO HV ISO 68

Industrial Hydraulic Oil



Meets the requirements:
SAE MS 1004, ISO Viscosity Grade 68, DIN 51524-2 (HM), DIN 51524-3 (HVLP), ISO 11158 (HM, HV, HVLP), ASTM USA D6158, ANSI AGMA 9005-E02-RO, AIST 126/127, JCMAS P041 HK Hydraulic specification, GERMAN STEEL INDUSTRY SEB 181222, BOSCH REXROTH RE 90220, EATON M-2950-S, EATON I-286-S3, GM Ls2, MAG CINCINNATI P-68, MAG CINCINNATI P-69, MAG CINCINNATI P-70, PARKER DENISON HF-0/-1/-2, SPERRY VICKERS M-2950-S, SPERRY VICKERS I-286-S3

All-season mineral paraffin hydraulic oils with a high-viscosity index created for the hydraulic equipment of a mobile or stationary equipment operating at high and extra-high operating temperatures. It was developed taking into account the requirements for industrial hydraulic systems operating in the conditions of extra-high loads, pressures, temperatures and/or velocities and especially in the conditions of strongly varying temperatures.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	62.8
Viscosity at 100 °C	D 445	cSt	11.5
Viscosity index	D 2270		180
Flash point COC	D 92	°C	220
Pour point	D 97	°C	-40
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-

Volume:

10L	MN2203-10	208L	MN2203-DR
20L	MN2203-20	1000L	MN2203-IBC
60L	MN2203-60		

www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®