

Product Code:

2602

TO-4

Powertrain Oil

Transmission Oil

Meets the requirements:

SAE 30, ALLISON C4 (off-road), CATERPILLAR TO-4,
KOMATSU KES 07.868.1

A special all-season transmission-hydraulic mineral oil designed for use in hydraulic systems, transmissions and gearboxes (including power ones), on-board gearboxes of other devices of off-road equipment with and without low-load brakes (clutches).

It complies with strict Cat TO-4, requirements imposed for TDTO (Transmission/Drive Train Oil) lubricants by the Caterpillar company. The specification TO-4 is the industry standard. The specification determines operating requirements imposed on hydraulic fluids for their use in CAT equipment.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/m³	890
Viscosity at 40 °C	D 445	CSt	88,72
Viscosity at 100 °C	D 445	CSt	10,68
Viscosity index	D 2270		104
Flash point	D 92	°C	220
Pour point	D 97	°C	-33
Brookfield dynamic viscosity at -25 °C max	D 5293	°C	140000
TBN	D 2896	mgKOH/g	7,50

Volume:

20L MN2602-20 208L MN2602-DR

1000L MN2602-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®