

Product Code:

2701

MULTI UTTO WB 101

Universal Tractor Transmission Oil

Meets the requirements:

SAE 10W-30, API GL-4, DIN 51524-2, ALLISON C4,
VOLVO VCE WB 101, 97303, CATERPILLAR TO-2,
ZF TE-ML 03E, TE-ML 05F, TE-ML 06E, TE-ML 06F, TE-ML 06K,
ZF TE-ML 17E, TE-ML 21F, PARKER DENISON HF-0/HF-1/HF-2,
CASE I H MS 1204, MS 1206, MS 1207, MS 1209
FORD NEW HOLLAND ESN-M2C41-B/ESN-M2C86-A,
FORD NEW HOLLAND ESN-M2C86-B/ESN-M2C86-C,
FORD NEW HOLLAND ESN-M2C134-A/ESN-M2C134-C,
FORD NEW HOLLAND ESN-M2C134-D, EATON I-280-S,
SPERRY VICKERS M-2950-S, I-280-S, EATON M-2950-S,
MASSEY FERGUSON M 1135, M 1143, M 1145, KUBOTA UDT Fluid,
NEW HOLLAND NH 420A, NH 410B, JOHN DEERE 20C,
SAUER SUNDSTRAND DANFOSS Hydro Static Trans Fluid

A universal and multi-functional mineral all-season tractor oil for farm holdings and tractors, agricultural vehicles with very high operating characteristics. Its main purpose: an oil for on-board gearboxes with a standard replacement interval. It complies with Volvo 97303 requirements. It is also suitable for mechanical gearboxes with and without synchronizers, transmissions (including power transmissions), back axles, hydraulic systems (including the ones integrated with a mechanical gearbox) and other equipment that requires Universal Tractor Transmission Oil (UTTO) grade oil. It is particularly suitable for the reduction of vibration in "wet" brake systems and power-take off.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	54.71
Viscosity at 100 °C	D 445	cSt	9.09
Viscosity index	D 2270		147
Flash point COC	D 92	°C	220
Pour point	D 97	°C	-45
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	9.17



Volume:

10L	MN2701-10	60L	MN2701-60
20L	MN2701-20	208L	MN2701-DR
		1000L	MN2701-IBC

www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®