Product Code:

2903

COMPRESSOR OIL ISO 150



Meets the requirements:

ISO Viscosity Grade 150, DIN 51506 (VBL), DIN 51506 (VCL), DIN 51506 (VDL), ISO DP 6521 L-DAA, ISO DP 6521 L-DAB, ISO DP 6521 L-DAG, ISO DP 6521 L-DAH

Highly-purified paraffin low-ash mineral compressor oil with an extended replacement age. It ensures a stable and continuous operation of the equipment throughout the entire operation period.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	890
Viscosity at 40 °C	D 445	cSt	144.4
Viscosity at 100 °C	D 445	cSt	14.55
Viscosity index	D 2270		99
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-25
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-

Volume:

10L	MN2903-10	60L	MN2903-60
20L	MN2903-20	208L	MN2903-DR

www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®