

Product Code:

3103

M.O. SAE 30

Monograde Mineral Engine Oil

Meets the requirements:

SAE 30, API CH-4, MIL L 2104 C, CATERPILLAR Series 3,
DAVID BROWN DB OM 616, MACK EO-J, VOLVO B20

A special highest-quality monograde mineral engine oil for heavy-load diesel-powered engines with and without a turbocharger operating under various conditions at ambient temperatures more than -15 °C. It was designed especially for VOLVO and CATERPILLAR equipment that requires the presence of corresponding specifications.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/m³	880
Viscosity at 40 °C	D 445	CSt	108.31
Viscosity at 100 °C	D 445	CSt	12.44
Viscosity index	D 2270		107
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-28
Total base no.	D 2896	mgKOH/g	9.20
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-

Volume:

10L	MN3103-10	208L	MN3103-DR
20L	MN3103-20	1000L	MN3103-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®