

Product Code:

3104

M.O. SAE 40

Industrial Hydraulic Oil

Meets the requirements:

SAE 40, API CH-4, MIL L 2104 C,
CATERPILLAR Series 3, MTU Type 2,
MACK EO-J, VOLVO B20,
ZF TE-ML 02C/04B,
DAVID BROWN DB OM 616

A special monograde mineral engine oil for heavy-load diesel-powered engines with and without a turbocharger operating under various conditions at ambient temperatures more than -20 °C. It was designed especially for VOLVO and CATERPILLAR equipment that requires the presence of corresponding specifications.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/m³	870
Viscosity at 40 °C	D 445	CSt	106,81
Viscosity at 100 °C	D 445	CSt	13,81
Viscosity index	D 2270		129
Pour point, max	D 97	°C	-30
Flash point	D 92	°C	224
TBN	D 2896	mgKOH/g	8,20

Volume:

10L	MN3104-10	208L	MN3104-DR
20L	MN3104-20	1000L	MN3104-IBC
60L	MN3104-60		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®