

Product Code:

4012

AF12+ ANTIFREEZE

Ready-to-use Longlife Coolant Fluid
-40 °C/+125 °C

Meets the requirements:

SAE J1034, JASO M325, AFNOR FRANCE NF R15-601 (except for RA), ASTM USA D3306/D4656/D4985/D6210, BSI GB BS 6580:2010, FVV GERMANY Heft R443, KSM SOUTH KOREA 2142, NATO S-759, MIL BELGIUM BT-PS-606-A, MIL FRANCE DCSEA 615/C, MIL ITALY E/L-1415B, MIL SWEDEN FSD 8704, OENORM AUSTRIA V5123, UNE SPAIN 26-361-88/1, ADE, ASTON MARTIN, VW TL 774 D/774 F, BEHR, BERGEN ENGINES 2.13.01, BMW GS 94000, BRB BR 637, CASE NEW HOLLAND MAT 3624, CATERPILLAR MAK A4.05.09.01, CHEVROLET, CLAAS, CUMMINS CES 14439/14603, GREAT WALL, CUMMINS IS series N14, DAF 74002, DETROIT DIESEL 93K217, FENDT, FORD WSS-M97B44-D, HITACHI, ISUZU, JAGUAR CMR 8229, JAGUAR STJLR.651.5003, JENBACHER TA 1000-0201, JOHN DEERE JDM H5, KAROSA, KOBELCO, KOMATSU 07.892 (2009), LAND ROVER STJLR.651.5003, LEYLAND TRUCKS DW03245403, LIEBHERR MD1-36-130, MACK 014 GS 17009, MAN 324 SNF, MAN B W A S, MAN B W DIESEL AG D36 5600, MAZDA MEZ MN 121 D, MB 326.3 (Premix), MB 325.3, MINI GS 94000, MITSUBISHI MHI, MTU MTL 5048, MWM 0199-99-2091/11, RENAULT 41-01-001/Type D

A carboxylated (organic - OAT Organic Acid Technology) ready-for-use solution, designed for a year-round use in any modern cooling systems for which the use of ethylene-glycol-based antifreeze is recommended. It ensures a reliable protection of any cooling system.

Product Characteristics:

Test	Unit	Result
Appearance		RED
Ethanol content	0%	0%
Alkalinity 0.1N HCL	2,6	3.40
Freezing point °C	-40	-40
Density at 20 °C	1.065-1.095	1.072
pH	7-9	8.70

Volume:

1L	MN4012-1	60L	MN4012-60
5L	MN4012-5	208L	MN4012-DR
10L	MN4012-10	1000L	MN4012-IBC
20L	MN4012-20		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®