

Product Code:

4013

AG13 ANTIFREEZE

Ready-to-use Hightec Coolant Fluid

Meets the requirements:

SAE J1034, AFNOR FRANCE NF R15-601,
ASTM USA D3306, ASTM USA D4340,
ASTM USA D4985, BSI GB BS 6580:2010,
NATO S-759, BMW GS 94000, CHRYSLER MS-7170,
FORD ESE-M978B4H-A, FORD AF Plus, GM 1825 M,
GM 1899 M, GM SATURN, JAGUAR, JOHN DEERE,
JENBACHER TA 1000-0204, MAN 324 Typ NF,
JENBACHER TA 1000-0201, MINI GS 94000,
MB 325.0, MTU MTL 5048, OPEL GME L1301,
OPEL GM Q1130100, VAUXHALL GME L1301

A hybrid (HOAT - Hybrid Organic Acid Technology) high-technology ready-to-use solution (which does not require dilution and protects the car cooling system at temperatures down to -40 °C) with excellent operating characteristics intended for a year-round use in any modern cooling system for which the use of mono-ethylene-glycol-based antifreeze is recommended. It ensures a reliable protection of any cooling system.

Product Characteristics:

Test	Method	Unit	Result
Appearance			GREEN
Ethanol content		%	0%
Freezing point		°C	-40
Density at 20 °C		kg/l	1.073
pH		°C	8.52
Reserve alkalinity, min		ml	2.6

Volume:

1L	MN4013-1	60L	MN4013-60
5L	MN4013-5	208L	MN4013-DR
10L	MN4013-10	1000L	MN4013-IBC
20L	MN4013-20		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®