

Product Code:

4112

AF12+ ANTIFREEZE

Concentrated Longlife Coolant Fluid

Meets the requirements:

SAE J1034, JASO M325, ASTM USA D3306, ASTM USA D4656, ASTM USA D4985, ASTM USA D 6210, BSI GB BS 6580:2010, AFNOR FRANCE NF R15-601 (except for RA), NATO S-759, FVV GERMANY Heft R443, KSM SOUTH KOREA 2142, KOBELCO, MIL BELGIUM BT-PS-606-A, MIL FRANCE DCSEA 615/C, MIL ITALY E/L-1415B, MIL SWEDEN FSD 8704, ADE, CLAAS, OENORM AUSTRIA V5123, UNE SPAIN 26-361-88/1, BEHR, ASTON MARTIN, VW TL 774 D/F, BERGEN ENGINES 2.13.01, BMW GS 94000, BRB BR 637, CASE NEW HOLLAND MAT 3624, CATERPILLAR MAK A4.05.09.01, CHEVROLET, FENDT, CUMMINS CES 14439/14603, CUMMINS IS series N14, DACIA 41-01-001 / 41-01-001-T, DAF 74002, GREAT WALL, DETROIT DIESEL DFS 93K217, FORD WSS-M97B44-D, HITACHI, ISUZU, JAGUAR CMR 8229/STJLR.651.5003, JENBACHER TA 1000-0201, JOHN DEERE JDM H5, KAROSA, KOMATSU 07.892 (2009), LAND ROVER STJLR.651.5003, LEYLAND TRUCKS Dw03245403, LIEBHERR MD1-36-130, MACK 014 GS 17009, MAN 324 Typ SNF, MAN B W A S, MAN B W DIESEL AG D36 5600, MAZDA MEZ MN 121 D, MB 325.3, MITSUBISHI MHI, MTU MTL 5048, MTU MTL 5048, MWM 0199-99-2091/11, MITSUBISHI MHI, MWM 0199-99-2091/11

A carboxylated (organic - OAT Organic Acid Technology) concentrated antifreeze intended for a year-round use in any modern cooling system for which the use of ethylene-glycol-based antifreeze is recommended.

Product Characteristics:

Test	Method	Unit	Result
Appearance			RED
Density at 20 °C		°C	1.115
pH (50 % vol.)		%	8.60
Freezing point °C (50 % dilution by vol.)		%	-35
Ethanol content			0%
Alkanility 0.1N HCL			9.1
Boiling point, min		°C	163



Volume:

1L	MN4112-1	60L	MN4112-60
5L	MN4112-5	208L	MN4112-DR
10L	MN4112-10	1000L	MN4112-IBC
20L	MN4112-20		

www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®