

Product Code:

7106

TS-6 UHPD Eco

Synthetic Truck Engine Oil

Meets the requirements:

SAE 10W-40, API CI-4, ACEA E7, ACEA E4, MACK EO-N,
CUMMINS CES 20077, CUMMINS CES 20078, SCANIA LDF-3,
VOLVO VDS-3, RENAULT RLD-2, VOITH Class B,
DAIMLER DTFR 15B120, MAN M 3277, MTU Type 3

All-weather synthetic motor oil for heavy-duty and high-speed diesel engines of the latest generation with and without turbocharger, operating in severe conditions on low sulphur fuel. Designed specifically to protect machinery and benefit most out of it regardless of operating conditions.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	92.51
Viscosity at 100 °C	D 445	cSt	13.99
Viscosity index	D 2270		155
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-42
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	15.79
Dynamic viscosity at -25 °C, max	D 5293	cP(mPas)	5669
High-shear-rate viscosity at 150 °C	D 4741	cP	3.66

Volume:

10L	MN7106-10	60L	MN7106-60
20L	MN7106-20	208L	MN7106-DR
		1000L	MN7106-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®