

Product Code:

7107

TS-7 UHPD BLUE

Synthetic Truck Engine Oil

Meets the requirements:

SAE 10W-40, API CK-4/CJ-4, ACEA E8, ACEA E11, DAF (ACEA E6), IVECO (ACEA E6), CATERPILLAR ECF-3, CUMMINS CES 20086, DETROIT DIESEL DDC 93K222, MB 228.31, MAN M 3477/M 3775, RENAULT VI RLD-3, MTU DDC Type 3.1, MACK EOS-4.5, JASO DH2, DAIMLER DTFR 15C110, VOLVO VDS-4.5

All-weather synthetic motor oil for heavy-duty and high-speed diesel engines of the latest generation with and without turbocharger, operating in severe conditions on low sulphur fuel. The oil has successfully passed road and laboratory tests at VOLVO, Mercedes-Benz, MAN, MACK and RENAULT centres and has their written approvals.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	86.11
Viscosity at 100 °C	D 445	cSt	13.84
Viscosity index	D 2270		165
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-42
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	10.2
Dynamic viscosity at -25 °C, max	D 5293	cP(mPas)	4132

Volume:

5L	MN7107-5	60L	MN7107-60
7L	MN7107-7	208L	MN7107-DR
10L	MN7107-10	1000L	MN7107-IBC
20L	MN7107-20		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®