

Product Code:

7118

TS-18

Synthetic Truck Engine Oil

Meets the requirements:

SAE 15W-40, API CK-4, ACEA E8, ACEA E11, MB 228.31, MB 228.51, VOLVO VDS-4.5, CUMMINS CES 20086, MAN M 3775, IVECO (ACEA E6-2016), DAF (ACEA E6-2016), DETROIT DIESEL DDC93K222, RENAULT RLD-3, MACK EOS-4.5, CATERPILLAR ECF-3

All-weather synthetic motor oil for heavy-duty and high-speed diesel engines of the latest generation with and without turbocharger, operating in severe conditions on low sulphur fuel. Designed specifically to protect machinery and benefit most out of it regardless of operating conditions.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	98.98
Viscosity at 100 °C	D 445	cSt	14.20
Viscosity index	D 2270		147
Flash point COC	D 92	°C	230
Pour point	D 97	°C	-40
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	10.45
Dynamic viscosity at -20 °C, max	D 5293	cP(mPas)	3821
High-shear-rate viscosity at 150 °C	D 4741	cP	3.80

Volume:

10L	MN7118-10	60L	MN7118-60
20L	MN7118-20	208L	MN7118-DR
		1000L	MN7118-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®