

Product Code:

7125

TS-25 FA-4

Truck Engine Oil

Meets the requirements:

SAE 5W-30, API FA-4, CUMMINS CES 20087,
DETROIT DIESEL DFS 93K223, VOLVO VDS 5,
DAIMLER DTFR 15C130 Approval

Innovative energy-saving synthetic (contains PAO) low-viscosity engine oil developed for the latest generation of turbocharged diesel engines operating under severe conditions, using ultra-low sulphur fuel (15 ppm or less) and equipped with exhaust gas aftertreatment systems: SCR, EGR and DPF. Provides engine protection in accordance with EPA 2010 and GHG 17. Developed to meet the requirements of Volvo and Daimler.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	64.11
Viscosity at 100 °C	D 445	cSt	11.01
Viscosity index	D 2270		165
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-48
Dynasmic viscosity at -30 °C	D 5293	cP(mPas)	5076
Total base no.	D 2896	mgKOH/g	12.59
High shear rate viscosity at -150 °C	D 4741	cP	3.20
Noack volatility test mass/mass	D 5800	%	11.2
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-



Volume:

20L MN7125-20

208L MN7125-DR

1000L MN7125-IBC

www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®