

Product Code:

7205

2-TAKT UNIVERSAL

Universal 2-stroke Engine Oil

Meets the requirements:

API TC, JASO FB, ISO L-EGB

A universal high-quality mineral-based engine oil for modern high-load and high-speed 2-stroke engines with air cooling. It is suitable for the lubrication by a pre-mixed blend and an automatic mixing in an engine intake.

Product Characteristics:

Test	Method	Unit	Result
Color			GREEN
Density at 15 °C	D 1298	kg/l	880
Viscosity at 40 °C	D 445	CSt	80,69
Viscosity at 100 °C	D 445	CSt	10,25
Viscosity index	D 2270		108
Flash point	D 92	°C	110
TBN	D 2896	mgKOH/g	1,20
Pour point	D 97	°C	-30
Mechanical impurities	D 2273	%	-

Volume:

1L	MN7205-1	60L	MN7205-60
4L	MN7205-4	208L	MN7205-DR
10L	MN7205-10	1000L	MN7205-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®