

Product Code:

7404

SAFARI

Synthetic Blend Engine Oil

Meets the requirements:

SAE 20W-50, API SN/CH-4

Universal economy-class engine oil, which is a mixture of synthetic components and a high purity mineral base, for modern highly accelerated petrol and diesel engines with and without a turbocharger used in difficult operating conditions and engines with a very high mileage used in various operating conditions.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/m³	890
Viscosity at 40 °C	D 445	CSt	154,05
Viscosity at 100 °C	D 445	CSt	16,81
Dynamic viscosity at -15 °C	D 5293	CP	8136
Viscosity index	D 2270		117
Flash point COC	D 92	°C	232
Pour point	D 97	°C	-33
TBN	D 2896	mgKOH/g	6,65
High shear rate viscosity, at 150 °C	D 4741	cP	3,89
Ignition temperature		°C	350
Mechanical impurities D 2273		%	-

Volume:

1L	MN7404-1	20L	MN7404-20
4L	MN7404-4	60L	MN7404-60
5L	MN7404-5	208L	MN7404-DR
7L	MN7404-7	1000L	MN7404-IBC
10L	MN7404-10		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®