

Product Code:

7501

CLASSIC

HC Synthese Technology

Meets the requirements:

SAE 10W-40, API SN/CH-4, ACEA A3/B4, JASO MA2,
VW 505 00/502 00, VW 501 01/500 00, MB 229.3,
MB 229.1, PSA B71 2296, RENAULT RN0700/RN0710

Universal ester-containing HC-synthese engine oil for modern gasoline and diesel engines with and without a turbocharger, both multi-valve and direct injection, including "old" brands and high mileage vehicles. Designed according to the requirements of European manufacturers.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	112.05
Viscosity at 100 °C	D 445	cSt	15.77
Viscosity index	D 2270		150
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-38
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	8.1
Dynamic viscosity at -25 °C, max	D 5293	cP(mPas)	6832
Sulphate ash	D 874	% mass	1.22
High-shear-rate viscosity at 150 °C	D 4741	cP	3.70
Noakc volatility test, % max	D 5800	mass/mass	12.5

Volume:

1L	MN7501-1	20L	MN7501-20
4L	MN7501-4	60L	MN7501-60
5L	MN7501-5	208L	MN7501-DR
7L	MN7501-7	1000L	MN7501-IBC
10L	MN7501-10		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®