

Product Code:

7505

MOLIBDEN

Semi-synthetic oil with MOS₂,
for Petrol & Diesel Engines

Meets the requirements:

SAE 10W-40, API SN/CH-4, VW 501 01, VW 505 00

Universal motor oil on a hydro synthetic basis,
specially developed for all types of gasoline and
diesel engines, including heavy-duty engines.
Contains organic and inorganic molybdenum (MoS₂).

Product Characteristics:

Test	Method	Unit	Result
Color			BLACK
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	112
Viscosity at 100 °C	D 445	cSt	15,34
Viscosity index	D 2270		145
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-38
TBN	D 2896	mgKOH/g	9,15
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Dynamic viscosity at -25 °C	D 5293	[cP](mPas)	5459

Volume:

1L	MN7505-1	60L	MN7505-60
4L	MN7505-4	208L	MN7505-DR
5L	MN7505-5	1000L	MN7505-IBC
20L	MN7505-20		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®