

Product Code:

7507

DEFENDER

Semi - Synthetic Engine Oil

Meets the requirements:

SAE 10W-40, API SP, ACEA A3/B4, MB 229.3, MB 229.1,
VOLKSWAGEN 505 00/502 00/501 01/500 00, PSA B71 2294,
RENAULT RN0700, RENAULT RN0710, Fiat 955535-G2

Unique innovative fully synthetic premium engine oil with special anti-scuffing properties thanks to the addition of synthetic esters and hexagonal boron nitride h-BN (white graphite). Suitable for all types of car engines - diesel and petrol, four- and two-stroke.

- For turbocharged engines with direct injection, a unique oil formulation reduces to zero the effect of premature ignition of the fuel mixture LSPI (LowSpeed Pre-Ignition)

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	109.46
Viscosity at 100 °C	D 445	cSt	15.54
Viscosity index	D 2270		150
Flash point COC	D 92	°C	224
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	10.74
Dynamic viscosity at -25 °C, max	D 5293	cP(mPas)	6632
High shear rate viscosity at 150 °C, min	D 4741	cP	3.56

Volume:

1L	MN7507-1	20L	MN7507-20
4L	MN7507-4	60L	MN7507-60
5L	MN7507-5	208L	MN7507-DR
7L	MN7507-7	1000L	MN7507-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®