

Product Code:

7510

FAVORIT

Semi-synthetic Engine Oil

Meets the requirements:

SAE 15W-50
API SL/CH-4
MB 228.1/229.1
VW 501 01/505 00
MAN 271

MANNOL Favorit is a semi-synthetic multipurpose multigrade engine oil for modern gasoline and diesel engines with and without turbocharge. Provides safe engine lubrication at extreme loads. Prevents low-temperature sediments formation thus providing optimal oil feeding to the engine components. Contains low-ash additives to prolong the endurance of the catalyst.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m³	890
Viscosity at 40°C	D 445	CSt	147
Viscosity at 100°C	D 445	CSt	17,92
Viscosity at -20°C	D 5293	CP	6950
Viscosity index	D 2270		135
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-33
TBN	D 2896	gKOG/kg	7,07

Volume:

1L	MN7510-1	20L	MN7510-20
4L	MN7510-4	60L	MN7510-60
5L	MN7510-5	208L	MN7510-DR
10L	MN7510-10	1000L	MN7510-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®