

Product Code:

7511

ENERGY

Fully Synthetic Engine Oil

Meets the requirements:

SAE 5W-30, API SN/CH-4, ACEA A3/B4, VW 502 00, VW 505 00, VW 503 01, VW 501 01, MB 229.3, MB 229.5, BMW LL-98, RENAULT RN0710/RN0700, FORD WSS-M2C913-B

Innovative universal premium ester-containing engine oil for modern gasoline and diesel engines with and without turbocharging. Designed based on the requirements of European car manufacturers.

Product Characteristics:

Test	Method	Unit	Result
Density at 15 °C	D 1298	kg/l	850
Viscosity at 40 °C	D 445	cSt	73.60
Viscosity at 100 °C	D 445	cSt	12.02
Viscosity index	D 2270		160
Flash point COC	D 92	°C	220
Pour point	D 97	°C	-38
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-
Total base no.	D 2896	mgKOH/g	10.68
Dynamic viscosity at -30 °C, max	D 5293	cP(mPas)	5230
High-shear-rate viscosity at 150 °C	D 4741	cP	3.52

Volume:

1L	MN7511-1	20L	MN7511-20
4L	MN7511-4	60L	MN7511-60
5L	MN7511-5	208L	MN7511-DR
7L	MN7511-7	1000L	MN7511-IBC
10L	MN7511-10		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®